

ICW74

功能特点

ICW74:

光源:

Aiming: 617nm LED

625nm LED 红光照明

6700K LED 白光照明

远距离读码

(可选配: 柔光罩、偏振罩)



- 支持一维条码1-D
- 支持二维条码2-D
- 密封等级可达到IP65
- 可承受多次1.5米高度跌落到水泥地面的冲击 (允许偏转5°)
- 储存温度为-40°C to 70°C
- 识别精度: 1D (Code 39) : 3mil,
- 2D (QR) : 5mil ; 1mil=0.0254mm

参数	型号	ICW74L	ICW74Q	ICW74X	ICW74V
尺寸	52.5(width)X28.43(height)X43.14(depth)				
重量	70g				
供电方式	5V-30VDC +/-10%, 500mA				
功耗	peak <2.5W, average 2W				
功能模块	Dome illumination				
系统架构	ARM926				
图像数据格式	JPEG				
传感器类型	Global Shutter CMOS				
软件	固定读取一维/二维码	读取高速移动部件一维/二维码	读取具有挑战性一维/二维码, 包括DPM	专业支持Vericode	
读码距离	40mm,70mm,180mm				
分辨率	1280*800				
帧率	60 fps				
图像色彩	mono				
辅助光源	8 high brightness LED, Aiming: 617nm LED、625nm LED 红光照明, 6700K LED 白光照明				
角度	FOV-h: 40degree FOV-v: 35degree				
接口类型	RS232, USB-virtual-COM, USB-keyboard, Ethernet				
运动容差	2m/s				
识别精度	1D(C128) 2mil、2D(Datamatrix) 3mil;1mil=0.00254mm				
识读码制	1D code: Code 128, Code 39, Code 93, Code 11, Matrix 2 of 5, Interleaved 2 of 5, Codabar, MSI Plessey, GS1 DataBar, China Postal, UPC, EAN etc. 2D code: PDF 417, MicroPDF417, DataMatrix, Maxicode, QR code, MicroQR, Aztec, Hanxin, Vericode* etc.				
温度	Operating: -30°C to 60°C, Storage: -40°C to 70°C				
湿度	0% to 90% relative humidity no-condenssing				
IP等级	IP65				
...					