SHIJIE 视界
INTELLIGENT TECH
上海视界纵横智能科技有限公司

ICW92200N

二维扫码枪
Area-imaging Scanner

简洁大气外观设计
Simple Atmosphere Designs

Cost-effective

低功耗、性能强大
全面读取所有主流一维、二维码
快速读取手机屏幕条码
支持RS232接口和USB接口

Low Power Consumption, Strong Performance.
Read all Mainstream 1D/2D Barcodes.
Fast Mobile Phone Screen Barcode Reading.
Build in RS232 and USB Interface.

ICW92200N

技术规格书
Technical Specification

Physical Characteristics	
尺寸Dimensions:	170mm x 95mm x 70mm
重量Weight:	162.2g
电压Voltage :	5VDC
电流Current :	300mA (Operating)
Performance Characteristics	
传感器像素Image (Pixels):	640 pixels (H)x 480 pixels (V)
光源Light Source:	Aiming: 617 nm LED; illumination: 6500K LED
视场角Field of View:	40° (H) x 32° (V)
旋转倾斜偏转Roll / Pitch / Yaw:	360°, ±65°, ±60°
打印对比度Print Contrast:	25% minimum reflective difference
接口支持Interfaces Supported:	USB, RS232
Symbology Decode Capability	
一维条码1-D:	UPC, EAN, Code128, Code 39, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Codabar, MSI Plessey, GS1 DataBar, China Postal, Korean Postal, etc.
二维条码2-D:	PDF417, MicroPDF417, Data Matrix, Maxicode, QR Code, MicroQR, Aztec, Hanxin, etc.
User Environment	
工作温度Operating Temperature:	0°C to 50°C
存储温度Storage Temperature:	-40°C to 70°C
湿度Humidity:	0% to 95% relative humidity,non-condensing
抗震性Shock Specifications:	Designed to withstand 1.5m(5') drops
环境光免疫Ambient Light Immunity:	100.000 Lux.
Decode Ranges	
5MIL	30mm-90mm
13MIL	40mm-170mm
1D Minimal Resolution	4mil
Performance may be impacted by bar code quality and environmental conditions	